



The Quality & Management system governing the manufacture of this product is ISO 9001:2000 and ISO 14001:2004 certified.




Battery Model	Dimensions (mm) & weight (Kg)		Cold Cranking Amps			Volts	Thread size mm	Reserve Capacity - Minutes Discharged						Capacity - Ampere Hour*							
	Length	Width	Height	Weight	20°C (68°F)			0°C (32°F)	-18°C (0°F)	75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr
HZY-MR12-18	181	76	167	5.4	204	137	84	12	5	-	26	45	93	19.6	18.4	17	15.6	13.8	12.8	10.5	
HZY-MR12-26	168	178	124	8.0	301	217	142	12	5	-	41	66	144	28.8	27.0	25	22.9	20.4	18.8	15.5	
HZY-MR12-33	196	131	160	10.4	350	260	172	12	6	7.0	53	77	173	34.2	32.3	29	28.0	24.7	23.3	18.6	
HZY-MR12-44	198	167	157	13.0	450	337	220	12	6	12.0	80	115	242	45.3	41.6	39	37.0	33.1	29.4	24.3	
HZY-MR12-55	229	138	213	18.4	569	444	294	12	6	19.4	86	120	168	61.0	57.2	53	48.5	43.1	39.9	32.8	
HZY-MR12-70J	349	168	175	21.0	663	530	367	12	6	27	117	159	218	78.2	73.4	68	62.2	55.4	51.1	42.1	
HZY-MR12-65	272	165	188	21.5	708	573	400	12	6	32	135	180	251	86.3	81.0	75	68.6	61.1	56.4	46.4	
HZY-MR12-80	260	168	211	25.1	740	600	425	12	8	33	144	195	270	90.7	85.4	80	72.8	66.1	60.6	49.9	
HZY-MR12-100	306	168	211	29.3	820	715	520	12	8	45	174	230	324	110	104	96	87.8	78.1	72.2	59.4	
HZY-MR12-110	329	173	209	32.2	854	766	560	12	8	49	188	253	363	118	112	104	95.8	85.9	78.7	64.4	
HZY-MR12-120	409	177	225	36.0	917	835	650	12	8	61	225	288	414	138	130	120	110	97.7	90.2	74.3	
HZY-MR12-135	342	173	282	43.7	998	906	762	12	8	84	276	368	519	167	157	145	133	118	109	89.8	
HZY-MR12-150	483	170	242	45.5	1011	919	784	12	8	88	288	384	540	173	162	150	137	122	113	92.9	
HZY-MR12-160	530	209	214	53.7	1028	938	811	12	8	95	318	414	582	184	173	160	146	130	120	99.0	
HZY-MR12-200	522	242	220	63.4	1094	988	909	12	8	142	438	564	796	239	227	214	196	171	161	131	
HZY-MR12-230	521	270	205	69.5	1117	1007	940	12	8	167	528	678	915	282	265	245	224	199	184	152	
HZY-MR6-110	193	168	204	17.1	880	789	577	6	8	53	209	268	372	129	121	112	102	91	84	69	
HZY-MR6-160	298	171	226	26.5	1059	966	835	6	8	111	342	444	624	196	184	170	156	138	128	105	
HZY-MR6-180	260	181	246	29.6	1071	972	868	6	8	120	366	474	666	207	194	180	165	147	135	111	
HZY-MR6-200	323	178	226	30.2	1083	978	900	6	8	133	402	516	720	223	210	194	178	158	146	120	
HZY-MR6-225	244	188	275	33.8	1116	1007	927	6	8	147	462	602	828	253	238	220	201	179	165	136	
HZY-MR8-160	260	182	298	34.4	1045	955	829	8	8	103	330	432	597	181	170	157	144	128	118	97	

Battery Charging: Haze recommend the following charging profile to optimise cycle and battery life. Charging Voltage (max) 2.41vpc Charging Current Max 20 Hour Ah / 5 e.g. HZY-MR12.100 = 96/5 = 19.2A. It is recommended that the charging voltage be switch to Float (2.27-2.3vpc) when the battery is fully charged. (The above parameters apply to 20-25 °C

Cycle Life: To ensure maximum cycle life it is recommended that the battery be fully recharged as soon as possible after use. Cycle life is very dependant on the depth of discharge (DOD). The following is a guide to the number of cycles expected. 100% DOD - 220 cycles, 75% DOD - 295 cycles, 50% DOD - 475 cycles.

Dual Marine Terminal: Note the dual marine terminal is a SAE Automotive post with a secondary M8 stud. The M* stud must **NOT** be used for cranking amps.




Haze Battery Company keenly encourages environmental awareness; PLEASE follow guidelines for the recycling /disposal of lead.

190706



UL Recognised Component
MH28512



Website: www.hazebattery.com
E mail : sales@hazebattery.com